




GE25-XL-KTT-B-L402/70-OSE

Radial insert ball bearing

Radial insert ball bearing GE...-XL-KTT-B-
OSE

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L402/70	L402/70
-----------	---------	---------

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D SP	52 mm	Outside diameter
B	34,9 mm	Width
C 0r	7.800 N	Basic static load rating, radial
C r	14.900 N	Basic dynamic load rating, radial
≈m	0,185 kg	Masa

Dimensions

C	15 mm	Width, outer ring
C 2	21,4 mm	Sealing total width
S	17,5 mm	Distance raceway
d 1	33,821 mm	Rib diameter inner ring
D 1	42,5 mm	Outside diameter seal
C a	3,9 mm	Distance to lubrication hole

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Nieosiowość statyczna