




GE45-SX

Spherical plain bearing

Angular contact spherical plain bearing,
requiring maintenance, sliding contact
surface: steel/steel, DIN ISO 12240-2, open
design

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance	Maintenance required	
Coating	Durotect M	Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	45 mm	Inner diameter bearing
D	75 mm	Outside diameter bearing
T	20 mm	Height
C _r	138.000 N	Basic dynamic load rating, radial
C _{0r}	532.000 N	Basic static load rating, radial
≈m	0,414 kg	Masa

Mounting dimensions

r _{1smin}	1 mm	Edge Spacing
r _{2smin}	0,3 mm	Edge Spacing
d _{a max}	51,7 mm	Connection measure Inner ring
D _{a min}	58 mm	Housing Connection Diameter
D _{b min}	67 mm	Connection diameter



Dimensions

d _K	66 mm	Ball diameter
D ₁	52,9 mm	Inner diameter of housing washer
B	19 mm	Width Inner ring
C	19 mm	Width Outer ring
s	1,5 mm	Plane Surface Spacing
A	10 mm	Distance lubrication Bore
α	1,7 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,012 mm	Bore diameter bearing, lower tolerance
D _{OT}	0 mm	Outer diameter, upper tolerance
D _{UT}	-0,016 mm	Outside diameter, lower tolerance
T _{OT}	0,25 mm	Height, upper tolerance
T _{UT}	-0,25 mm	Height, lower tolerance
C _{UT}	0 mm	Width outer ring, upper tolerance
C _{OT}	-0,24 mm	Width outer ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,24 mm	Width inner ring, lower tolerance
d ₂	60 mm	Connection measure Inner ring

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna