
**GN203-XL-KRR-B**

Radial insert ball bearing

Radial insert ball bearing GN..-KRR-B

X-life

Informacje techniczne

**Main Dimensions & Performance Data**

d	55,562 mm	Bore diameter
d	55,563 mm	Bore diameter, inch
D _{SP}	120 mm	Outside diameter
B	50,4 mm	Width
C _{0r}	44.500 N	Basic static load rating, radial
B ₁	67,5 mm	Locking collar total width
C _r	72.000 N	Basic dynamic load rating, radial
≈m	3,11 kg	Masa

Dimensions

C	31 mm	Width, outer ring
C ₂	34,5 mm	Sealing total width
S	22 mm	Distance raceway
d ₁	73,8 mm	Rib diameter inner ring
D ₁	100 mm	Outside diameter seal
C _a	10 mm	Distance to lubrication hole
d ₃	82,6 mm	Outside diameter locking collar/locknut



Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna