


GNE60-XL-KRR-B

Radial insert ball bearing

Radial insert ball bearings GNE...KRR-B,
spherical outer ring, location by eccentric
locking collar, R seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	60 mm	Bore diameter
D _{SP}	130 mm	Outside diameter
B	52 mm	Width
C _{0r}	52.000 N	Basic static load rating, radial
C _{ur}	2.460 N	Fatigue load limit, radial
B ₁	68 mm	Locking collar total width
C _r	82.000 N	Basic dynamic load rating, radial
≈m	2,642 kg	Masa

Dimensions

C	33 mm	Width, outer ring
C ₂	37,2 mm	Sealing total width
S	23 mm	Distance raceway
d ₁	79,4 mm	Rib diameter inner ring
D ₁	109 mm	Outside diameter seal
C _a	11,2 mm	Distance to lubrication hole
d ₃	89 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats



Calculation factors

f_0	13,2	Calculation factor
-------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna