





FAG

HC6330-G

Deep groove ball bearing

Deep groove ball bearing HC63.-G, Hybrid bearing, single row, generator bearing, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Material Bearing	HC	Hybrid bearing, rolling elements ceramic, bearing rings made of steel
Changed internal design	G	Generator bearing
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	65 mm	Width
C _r	330.000 N	Basic dynamic load rating, radial
C _{0r}	380.000 N	Basic static load rating, radial
C _{ur}	9.800 N	Fatigue load limit, radial
n _G	3.350 1/min	Limiting speed
n _{gr}	2.900 1/min	Reference speed
≈m	20,1 kg	Masa



Mounting dimensions

$d_{a \min}$	167 mm	Minimum diameter shaft shoulder
$D_{a \max}$	303 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	266,2 mm	Shoulder diameter outer ring
d_1	205,5 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	18	Calculation factor
-------	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Izolowane
	Łożysko gabarytowe