

FAG




HCM7014-E-T-P4S-UL-XL

High speed spindle bearing

High speed spindle bearing HCM70..-E,
adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, with ceramic balls, restricted tolerances

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	110 mm	Outside diameter
B	20 mm	Width
C _r	26.500 N	Basic dynamic load rating, radial
C _{0r}	15.100 N	Basic static load rating, radial
C _{ur}	1.210 N	Fatigue load limit, radial
n _G Grease	22.000 1/min	Limiting speed for grease lubrication
n _G Oil	32.000 1/min	Limiting speed for oil lubrication
≈m	0,559 kg	Masa



Mounting dimensions

d_a	77 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	102 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
$E_{tk \min}$	84,3 mm	Minimum diameter injection pitch
$E_{tk \max}$	87,2 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	80,7 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	87,2 mm	Maximum diameter injection pitch
a	31 mm	Distance between the apexes of the pressure cones

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



Additional information

F_{VL}	176 N	Preload force light
F_{VM}	460 N	Preload force medium
F_{VH}	956 N	Preload force heavy
K_{aEL}	503 N	Lift-off force light
K_{aEM}	1.331 N	Lift-off force medium
K_{aEH}	2.804 N	Lift-off force heavy
c_{aL}	138 N/ μ m	Axial rigidity light
c_{aM}	193 N/ μ m	Axial rigidity medium
c_{aH}	252 N/ μ m	Axial rigidity heavy

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia