




FAG

HCS71920-E-T-P4S-UL [🔗](#)

High speed spindle bearing

High speed spindle bearing HCS719...-E, adjusted, in pairs or sets, contact angle  $\alpha = 25^\circ$ , with ceramic balls, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

|                         |      |                                                                  |
|-------------------------|------|------------------------------------------------------------------|
| Preload                 | L    | Preload light                                                    |
| Contact angle           | E    | Contact angle $25^\circ$                                         |
| Sealing                 | 2RSD | Non-contact sealed on both sides and greased "for life"          |
| Cage                    | T    | Laminated fabric cage                                            |
| Tolerance class         | P4S  | Tolerance class P4S, FAG standard better than P4 to ISO 492:2023 |
| Arrangement bearing set | U    | Single bearing                                                   |

Main Dimensions & Performance Data

|                          |              |                                       |
|--------------------------|--------------|---------------------------------------|
| d                        | 100 mm       | Bore diameter                         |
| D                        | 140 mm       | Outside diameter                      |
| B                        | 20 mm        | Width                                 |
| C <sub>r</sub>           | 27.000 N     | Basic dynamic load rating, radial     |
| C <sub>0r</sub>          | 21.200 N     | Basic static load rating, radial      |
| C <sub>ur</sub>          | 1.560 N      | Fatigue load limit, radial            |
| n <sub>G</sub><br>Grease | 15.000 1/min | Limiting speed for grease lubrication |
| ≈m                       | 0,808 kg     | Masa                                  |



### Mounting dimensions

|               |        |                                                   |
|---------------|--------|---------------------------------------------------|
| $d_a$         | 107 mm | Diameter shaft shoulder                           |
| $d_a$         | H12    | Diameter shaft shoulder clearance                 |
| $D_a$         | 133 mm | Shoulder diameter outer ring                      |
| $D_a$         | H12    | Shoulder diameter outer ring clearance            |
| $r_{a \max}$  | 0,6 mm | Maximum recess radius                             |
| $r_{a1 \max}$ | 0,6 mm | Maximum recess radius                             |
| $a$           | 38 mm  | Distance between the apexes of the pressure cones |

### Dimensions

|            |        |                           |
|------------|--------|---------------------------|
| $r_{\min}$ | 1,1 mm | Minimum chamfer dimension |
| $r_1 \min$ | 1,1 mm | Minimum chamfer dimension |
| $\alpha$   | 25 °   | Contact angle             |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 80 °C  | Operating temperature max. |

### Additional information

|           |          |                       |
|-----------|----------|-----------------------|
| $F_{VL}$  | 109 N    | Preload force light   |
| $F_{VM}$  | 328 N    | Preload force medium  |
| $F_{VH}$  | 656 N    | Preload force heavy   |
| $K_{aEL}$ | 313 N    | Lift-off force light  |
| $K_{aEM}$ | 951 N    | Lift-off force medium |
| $K_{aEH}$ | 1.927 N  | Lift-off force heavy  |
| $c_{aL}$  | 162 N/μm | Axial rigidity light  |
| $c_{aM}$  | 239 N/μm | Axial rigidity medium |
| $c_{aH}$  | 307 N/μm | Axial rigidity heavy  |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne