

**HK2010-B** **Drawn cup needle roller bearing open end**

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Informacje techniczne**Twoja aktualna wersja produktu**

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	20 mm	Under roller diameter
D	26 mm	Outside diameter
C	10 mm	Width
C_r	6.400 N	Basic dynamic load rating, radial
C_{0r}	8.200 N	Basic static load rating, radial
C_{ur}	1.060 N	Fatigue load limit, radial
n_G	12.700 1/min	Limiting speed
$n_{G \text{ Grease}}$	7.600 1/min	Limiting speed for grease lubrication
n_{gr}	10.000 1/min	Reference speed
$\approx m$	10,92 g	Masa

Dimensions

$r_{\min}$	0,8 mm	Minimum chamfer dimension
------------	--------	---------------------------



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD20X26X4	Sealing ring
G20X26X4	Sealing ring 2

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy