
**HK2020-2RS**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK...-2RS, lip seals on both sides, to DIN 618

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	2RS	Contact seal on both sides

Main Dimensions & Performance Data

F_w	20 mm	Under roller diameter
D	26 mm	Outside diameter
C_r	12.700 N	Basic dynamic load rating, radial
C_{0r}	20.100 N	Basic static load rating, radial
C_{ur}	2.550 N	Fatigue load limit, radial
n_G	7.600 1/min	Limiting speed
n_G Grease	7.600 1/min	Limiting speed for grease lubrication
$\approx m$	22,47 g	Masa

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.



Additional information

LR17X20X20,5	Suitable inner rings LR
IR17X20X20-XL	Suitable inner rings IR

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie dwustronne



Mala przestrzeń zabudowy