


KGBAO12-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Size Code	12
Seal	PP
Relubrication	AS

Technical data

	4	Ball rows
≈m	64,6 g	Masa

Main Dimensions & Performance Data

F w	12 mm	Diameter of ball complement
H	30,5 mm	Height
L	32 mm	Length
Tol L	h12	Tolerance
B	42 mm	Width
C	600 N	Load capacity dyn. C
C 0	445 N	Load capacity stat. C0



Mounting dimensions

J B	32 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
A 5	21 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	7,7 mm	
L 4	32 mm	
L 5	20 mm	
J L	23 mm	
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
H 2	18 mm	Height shaft
Tol H 2	+ 0,01 mm	Upper tolerance
Tol H 2	- 0,01 mm	Lower tolerance
A 3	7,8 mm	
H 6	4,8 mm	
Tol H 6	- 0,5 mm	Tolerance
N 1	4,7 mm	
N 3	8 mm	
K 5	M4	
K 8	NIPA1	Lubrication nipple
W 1	2 mm	Width across flats
M W 1 max	1 Nm	Max. tightening torque
α	78 °	Angle