



15.09.2026, 08:09:39 UTC


SCHAEFFLER

KGBAO20-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Size Code	20
Seal	PP
Relubrication	AS

Technical data

	5	Ball rows
≈m	0,17 kg	Masa

Main Dimensions & Performance Data

F W	20 mm	Diameter of ball complement
H	44,5 mm	Height
L	45 mm	Length
Tol L	h12	Tolerance
B	60 mm	Width
C	1.600 N	Load capacity dyn. C
C 0	1.280 N	Load capacity stat. C0

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje



Mounting dimensions

J B	45 mm	
Tol J B	+ 0,15 mm	Upper tolerance
Tol J B	- 0,15 mm	Lower tolerance
A 5	30 mm	
Tol A 5	+ 0,01 mm	Upper tolerance
Tol A 5	- 0,01 mm	Lower tolerance
B 2	10 mm	
L 4	42 mm	
L 5	28 mm	
J L	32 mm	
Tol J L	+ 0,15 mm	Upper tolerance
Tol J L	- 0,15 mm	Lower tolerance
H 2	25 mm	Height shaft
Tol H 2	+ 0,01 mm	Upper tolerance
Tol H 2	- 0,01 mm	Lower tolerance
A 3	11 mm	
H 6	6,7 mm	
Tol H 6	- 0,5 mm	Tolerance
N 1	4,7 mm	
N 3	8 mm	
K 5	M4	
K 8	NIPA1	Lubrication nipple
W 1	2,5 mm	Width across flats
M W 1 max	1,5 Nm	Max. tightening torque
α	60 °	Angle