


KSR20-B0-10-10-17-15

Roller chain idler sprocket unit

Roller chain idler sprocket units KSR...B0, sprocket made from steel or sintered iron

Informacje techniczne



Main Dimensions & Performance Data

|     |          |                                 |
|-----|----------|---------------------------------|
| d   | 20 mm    | Bore diameter                   |
| d   | 0,018 mm | Upper tolerance                 |
| d   | 0 mm     | Lower tolerance                 |
| C 1 | 8,7 mm   | Thickness of sprocket           |
| D 0 | 86,3 mm  | Pitch circle diameter (gearing) |
| D k | 93,1 mm  | Tip diameter (gearing)          |
| ≈m  | 0,37 kg  | Masa                            |

Mounting dimensions

|   |              |                    |
|---|--------------|--------------------|
| p | 15,875 mm    | Tooth set          |
| z | 17           | Number of teeth    |
|   | x            | ISO chain          |
|   | x            | ANSI chain         |
| W | M6 X 0,75 mm | Width accros flats |



Dimensions

|     |        |                                           |
|-----|--------|-------------------------------------------|
| C 2 | 1,3 mm | Chamfer width                             |
| D   | 47 mm  | Outside diameter                          |
| B 1 | 31 mm  | Locking collar total width                |
| C   | 14 mm  | Width, outer ring                         |
| d 3 | 33 mm  | Outside diameter locking collar/locknut   |
| d 3 | 33 mm  | Outside diameter eccentric locking collar |
| W   | 3 mm   | Width of flats                            |
| B 1 | 31 mm  | Locking collar width                      |