


KTBO12-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; open design, sealed, greased, with relubrication facility; corrosion-resistant design possible

Informacje techniczne



Twoja aktualna wersja produktu

Size Code	12
Seal	PP
Relubrication	AS

Main Dimensions & Performance Data

F _W	12 mm	Diameter of ball complement
H	30 mm	Height
L	76 mm	Length
B	42 mm	Width
C	980 N	Load capacity dyn. C
C ₀	890 N	Load capacity stat. C0
≈m	0,26 kg	Masa



Mounting dimensions

J _B	30 mm	
Tol J _B	+ 0,15 mm	Upper tolerance
Tol J _B	- 0,15 mm	Lower tolerance
B ₂	7,7 mm	
J _L	40 mm	
Tol J _L	+ 0,15 mm	Upper tolerance
Tol J _L	- 0,15 mm	Lower tolerance
H ₂	18 mm	Center Height
Tol H ₂	+ 0,015 mm	Upper tolerance
Tol H ₂	- 0,015 mm	Lower tolerance
A ₃	6 mm	
T ₅	13 mm	
H ₆	25 mm	
N ₁	5,3 mm	
N ₃	10 mm	
G ₂	M6	Thread size
G ₃	M6	Thread size
α	78 °	Angle
K ₅	M5	Screw DIN 6912