


KTFS16-PP-AS

Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; with self-aligning linear ball bearing, sealed, greased, with relubrication facility

Informacje techniczne



Twoja aktualna wersja produktu

Size Code	16
Seal	PP
Relubrication	AS

Technical data

	8	Ball rows
≈m	0,255 kg	Masa

Main Dimensions & Performance Data

F _W	16 mm	Diameter of ball complement
H	40 mm	Height
L	78 mm	Length
B	50 mm	Width
C _{min}	1.790 N	Load capacity dyn. C
C _{0 min}	1.900 N	Load capacity stat. C0



Mounting dimensions

J _B	38 mm	
Tol J _B	+ 0,15 mm	Upper tolerance
Tol J _B	- 0,15 mm	Lower tolerance
L ₄	50 mm	
L ₅	10 mm	
J _{L4}	39 mm	Distance
D ₁	35 mm	Diameter
Tol D ₁	g7	Tolerance
D ₂	35 mm	Diameter
Tol D ₂	- 0,1 mm	Upper tolerance
Tol D ₂	- 0,3 mm	Lower tolerance
J _H	28 mm	
Tol J _H	+ 0,15 mm	Upper tolerance
Tol J _H	- 0,15 mm	Lower tolerance
T ₅	18 mm	Thread depth
G ₂	M8	Thread size
N ₁	6,6 mm	Diameter
K ₅	M6	
G ₃	M8x1	Thread size