
**LR202-X-2RSR**

Yoke type track roller

Yoke type track rollers LR2...-2RS/2RSR, single row self-retaining ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lip seal on both sides, with axial sealing action/with radial sealing action

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RSR	Lip seal on both sides, with radial sealing action
Outer ring profile	X	Cylindrical profile
Relubrication	Without	Without

Main Dimensions & Performance Data

D	40 mm	Outside diameter
d	15 mm	Bore diameter
C	11 mm	Height
C _{r w}	7.000 N	Basic dynamic load rating, radial
C _{0r w}	3.450 N	Basic static load rating, radial
C _{ur w}	175 N	Fatigue load limit, radial
n _{D G}	11.000 1/min	Speed on permanent grease lubrication
m	0,07 kg	Masa

Dimensions

d ₂	21 mm	Diameter of thrust washer
r _{min}	0,6 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne