






FAG

N1008-D-K-PVPA1-SP-XL

Cylindrical roller bearing

Super precision cylindrical roller bearings
N10..-D-K-PVPA1-SP-XL, Non-locating
bearing, with tapered bore, taper 1:12,
separable, with cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	PVPA1	PEEK-cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	D	Internal Variant D
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	15 mm	Width
C _r	25.000 N	Basic dynamic load rating, radial
C _{0r}	23.500 N	Basic static load rating, radial
C _{ur}	3.800 N	Fatigue load limit, radial
n _{G Grease}	27.500 1/min	Limiting speed for grease lubrication
n _{G Oil}	32.000 1/min	Limiting speed for oil lubrication
≈m	189 g	Masa



Mounting dimensions

d_a	49 mm	Diameter shaft shoulder
h_{12}		Diameter shaft shoulder tolerance
D_a	62,1 mm	Diameter of housing shoulder
H_{12}		Diameter of housing shoulder tolerance
$E_{tk1\text{ nom}}$	59,3 mm	Injection pitch diameter min
$E_{tk2\text{ nom}}$	52,5 mm	Injection pitch diameter nom
$r_{a1\text{ max}}$	0,6 mm	Maximum recess radius

Dimensions

$r_{1\text{ min}}$	0,6 mm	Minimum chamfer dimension
s_1	1,1 mm	Axial displacement
s_2	3,1 mm	Axial displacement
E	61 mm	Raceway diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia