



FAG


N1010-D-K-TVP-SP-XL

Cylindrical roller bearing

Super precision cylindrical roller bearings
N10..-D-K-TVP-SP, non-locating bearing,
with tapered bore, taper 1:12, separable, with
cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TVP	Plastic cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	D	Internal Variant D
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	80 mm	Outside diameter
B	16 mm	Width
C _r	36.500 N	Basic dynamic load rating, radial
C _{0r}	36.500 N	Basic static load rating, radial
C _{ur}	5.700 N	Fatigue load limit, radial
n _{G Grease}	14.200 1/min	Limiting speed for grease lubrication
n _{G Oil}	16.800 1/min	Limiting speed for oil lubrication
≈m	0,259 kg	Masa



Mounting dimensions

d _a	58,5 mm	Diameter shaft shoulder
h12		Diameter shaft shoulder tolerance
D _a	73,6 mm	Diameter of housing shoulder
H12		Diameter of housing shoulder tolerance
E _{tk 1 nom}	71,2 mm	Injection pitch diameter min
r _{a1 max}	0,6 mm	Maximum recess radius

Dimensions

r _{1 min}	0,6 mm	Minimum chamfer dimension
s ₁	3,1 mm	Axial displacement
s ₂	3,1 mm	Axial displacement
E	72,5 mm	Raceway diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia