



FAG

N222-E-XL-TVP2-C3

Cylindrical roller bearing

Cylindrical roller bearing N2...-E-TVP, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N2

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TVP2	Solid Window Cage made from PA66
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
C _r	345.000 N	Basic dynamic load rating, radial
C _{0r}	365.000 N	Basic static load rating, radial
C _{ur}	60.000 N	Fatigue load limit, radial
n _{G Grease}	4.000 1/min	Limiting speed for grease lubrication
n _{G Oil}	4.750 1/min	Limiting speed for oil lubrication
≈m	4,705 kg	Masa

Mounting dimensions

d _a	122 mm	Diameter shaft shoulder
D _a	188 mm	Diameter of housing shoulder
r _{a1 max}	2 mm	Maximum recess radius



Dimensions

r 1 min	2,1 mm	Minimum chamfer dimension
s 1	1,4 mm	Axial displacement
E	180,5 mm	Raceway diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia