



FAG

N306-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing N3..-E-M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N3

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	19 mm	Width
C _r	61.000 N	Basic dynamic load rating, radial
C _{0r}	48.000 N	Basic static load rating, radial
C _{ur}	7.700 N	Fatigue load limit, radial
n _G Grease	16.100 1/min	Limiting speed for grease lubrication
≈m	411,42 g	Masa

Mounting dimensions

d _a	37 mm	Diameter shaft shoulder
D _a	65 mm	Diameter of housing shoulder
r _{a1} max	1 mm	Maximum recess radius



Dimensions

r 1 min	1,1 mm	Minimum chamfer dimension
E	62,5 mm	Raceway diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia