



NA4868-XL

Needle roller bearing

Needle roller bearing NA...XL, single row,
with inner ring, outer ring with 2 bords

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (DIN 620-2)
Lubrication hole	With	
Coating	Without	
Lubricant	Without	

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	420 mm	Outside diameter
B	80 mm	Width
C _r	730.000 N	Basic dynamic load rating, radial
C _{0r}	1.940.000 N	Basic static load rating, radial
C _{ur}	255.000 N	Fatigue load limit, radial
n _G	1.270 1/min	Limiting speed
n _{gr}	620 1/min	Reference speed
≈m	24,2 kg	Masa



Dimensions

F	370 mm	Raceway diameter inner ring
r _{min}	2,1 mm	Minimum chamfer dimension
s	2 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy
-  Łożysko gabarytowe