


NA4901-2RSR-XL

Needle roller bearing

Needle roller bearings NA49...-2RSR,  
dimension series 49, lip seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|         |         |                             |
|---------|---------|-----------------------------|
| Sealing | 2RSR    | Contact seals on both sides |
| Coating | Without |                             |

Main Dimensions & Performance Data

|                       |              |                                       |
|-----------------------|--------------|---------------------------------------|
| d                     | 12 mm        | Bore diameter                         |
| D                     | 24 mm        | Outside diameter                      |
| B                     | 14 mm        | Width, inner ring                     |
| C <sub>r</sub>        | 8.600 N      | Basic dynamic load rating, radial     |
| C <sub>0r</sub>       | 8.300 N      | Basic static load rating, radial      |
| C <sub>ur</sub>       | 1.660 N      | Fatigue load limit, radial            |
| n <sub>G Grease</sub> | 13.900 1/min | Limiting speed for grease lubrication |
| ≈m                    | 27,3 g       | Masa                                  |

Dimensions

|                  |        |                             |
|------------------|--------|-----------------------------|
| F                | 16 mm  | Raceway diameter inner ring |
| C                | 13 mm  | Width, outer ring           |
| r <sub>min</sub> | 0,3 mm | Minimum chamfer dimension   |



### Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -20 °C | Operating temperature min. |
| $T_{max}$ | 100 °C | Operating temperature max. |

### Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Mała przestrzeń zabudowy