
**NATR6-X-PP-A** **Yoke type track roller**

Yoke type track rollers NATR...-PP-A, single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and an inner ring, axial guidance of outer ring is provided by the plastic axial plain washers and contact washers, three-stage sealing by plastic axial plain washer on both sides

Informacje techniczne**Twoja aktualna wersja produktu**

Sealing	PP	Three-stage sealing by plastic axial plain washer on both sides
Outer ring profile	X	Cylindrical profile
Relubrication	IR	Via inner ring

Main Dimensions & Performance Data

d	6 mm	Bore diameter
D	19 mm	Outside diameter
B	12 mm	Width of the bearing
C _{r w}	3.550 N	Basic dynamic load rating, radial
C _{0r w}	4.100 N	Basic static load rating, radial
C _{ur w}	560 N	Fatigue load limit, radial
n _{D G}	11.000 1/min	Speed on permanent grease lubrication
F _{0r per}	4.100 N	Permissible static load, radial
F _{r per}	4.100 N	Permissible dynamic load outer ring, radial
≈m	19,253 g	Masa

Dimensions

C	11 mm	Width, outer ring
d ₂	15 mm	Outside diameter of thrust washer
r _{min}	0,15 mm	Minimum chamfer dimension



Właściwości



Obciążenie promieniowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne