



FAG

NJ1022-XL-M1A-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ..-XL-M1A, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	170 mm	Outside diameter
B	28 mm	Width
C _r	167.000 N	Basic dynamic load rating, radial
C _{0r}	191.000 N	Basic static load rating, radial
C _{ur}	30.500 N	Fatigue load limit, radial
n _G	7.700 1/min	Limiting speed
n _{gr}	3.850 1/min	Reference speed
m	2,33 kg	Masa



Mounting dimensions

d _{a min}	116 mm	Minimum diameter shaft shoulder
d _{a max}	124 mm	Maximum diameter of shaft shoulder
D _{a max}	161 mm	Maximum diameter of housing shoulder
d _{c min}	133 mm	Minimum shaft shoulder
r _{a max}	2 mm	Maximum recess radius

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
r _{1 min}	1,1 mm	Minimum chamfer dimension
s	3,2 mm	Axial displacement
E	155 mm	Raceway diameter outer ring
F	125 mm	Raceway diameter inner ring
D _{1 min}	149,7 mm	Minimum rib diameter outer ring
d ₁	130,8 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.