



FAG

NJ1030-XL-M1 [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing NJ..-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	225 mm	Outside diameter
B	35 mm	Width
C _r	248.000 N	Basic dynamic load rating, radial
C _{0r}	310.000 N	Basic static load rating, radial
C _{ur}	47.000 N	Fatigue load limit, radial
n _G	5.800 1/min	Limiting speed
n _{gr}	3.100 1/min	Reference speed
≈m	4,86 kg	Masa



Mounting dimensions

d _{a min}	158 mm	Minimum diameter shaft shoulder
d _{a max}	167 mm	Maximum diameter of shaft shoulder
D _{a max}	215 mm	Maximum diameter of housing shoulder
d _{c min}	179 mm	Minimum shaft shoulder
r _{a max}	2,1 mm	Maximum recess radius

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	1,5 mm	Minimum chamfer dimension
s	4,1 mm	Axial displacement
E	205,5 mm	Raceway diameter outer ring
F	169,5 mm	Raceway diameter inner ring
D _{1 min}	199 mm	Minimum rib diameter outer ring
d ₁	176,6 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia