



FAG

NJ215-E-XL-MPAX-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ...-E-XL-MPAX, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	130 mm	Outside diameter
B	25 mm	Width
C _r	155.000 N	Basic dynamic load rating, radial
C _{0r}	157.000 N	Basic static load rating, radial
C _{ur}	28.000 N	Fatigue load limit, radial
n _G	9.800 1/min	Limiting speed
n _{gr}	4.400 1/min	Reference speed
≈m	1,44 kg	Masa



Mounting dimensions

d a min	84 mm	Minimum diameter shaft shoulder
d a max	87 mm	Maximum diameter of shaft shoulder
D a max	121 mm	Maximum diameter of housing shoulder
d c min	96 mm	Minimum shaft shoulder
r a max	1,5 mm	Maximum recess radius

Dimensions

r min	1,5 mm	Minimum chamfer dimension
r 1 min	1,5 mm	Minimum chamfer dimension
s	1,2 mm	Axial displacement
E	118,5 mm	Raceway diameter outer ring
F	88,5 mm	Raceway diameter inner ring
D 1 min	114,36 mm	Minimum rib diameter outer ring
d 1	94,35 mm	Maximum rib diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Additional information

HJ215-E	L-washer
---------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia