



FAG

NJ219-E-XL-MPAX-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ...-E-XL-MPAX, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	170 mm	Outside diameter
B	32 mm	Width
C _r	260.000 N	Basic dynamic load rating, radial
C _{0r}	265.000 N	Basic static load rating, radial
C _{ur}	45.000 N	Fatigue load limit, radial
n _G	7.200 1/min	Limiting speed
n _{gr}	3.650 1/min	Reference speed
m	3,188 kg	Masa



Mounting dimensions

d _{a min}	107 mm	Minimum diameter shaft shoulder
d _{a max}	111 mm	Maximum diameter of shaft shoulder
D _{a max}	158 mm	Maximum diameter of housing shoulder
d _{c min}	123 mm	Minimum shaft shoulder
r _{a max}	2 mm	Maximum recess radius

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	2,1 mm	Minimum chamfer dimension
s	0,7 mm	Axial displacement
E	154,5 mm	Raceway diameter outer ring
F	112,5 mm	Raceway diameter inner ring
D _{1 min}	148,62 mm	Minimum rib diameter outer ring
d ₁	120,45 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ219-E	L-washer
---------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia