



FAG

NJ2206-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	20 mm	Width
C _r	58.000 N	Basic dynamic load rating, radial
C _{0r}	50.000 N	Basic static load rating, radial
C _{ur}	7.900 N	Fatigue load limit, radial
n _G	21.200 1/min	Limiting speed
n _{gr}	8.000 1/min	Reference speed
≈m	0,293 kg	Masa



Mounting dimensions

d _a min	34 mm	Minimum diameter shaft shoulder
d _a max	37 mm	Maximum diameter of shaft shoulder
D _a max	56 mm	Maximum diameter of housing shoulder
d _c min	44 mm	Minimum shaft shoulder

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
s	1,6 mm	Axial displacement
E	55,5 mm	Raceway diameter outer ring
F	37,5 mm	Raceway diameter inner ring
D _{1 min}	52,45 mm	Minimum rib diameter outer ring
d ₁	41,25 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ2206-E L-washer

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia