



FAG

NJ2215-E-XL-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	130 mm	Outside diameter
B	31 mm	Width
C _r	192.000 N	Basic dynamic load rating, radial
C _{0r}	208.000 N	Basic static load rating, radial
C _{ur}	38.500 N	Fatigue load limit, radial
n _G	9.800 1/min	Limiting speed
n _{gr}	3.600 1/min	Reference speed
≈m	1,793 kg	Masa



Mounting dimensions

d _a min	84 mm	Minimum diameter shaft shoulder
d _a max	87 mm	Maximum diameter of shaft shoulder
D _a max	121 mm	Maximum diameter of housing shoulder
d _c min	96 mm	Minimum shaft shoulder

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
r _{1 min}	1,5 mm	Minimum chamfer dimension
s	1,6 mm	Axial displacement
E	118,5 mm	Raceway diameter outer ring
F	88,5 mm	Raceway diameter inner ring
D _{1 min}	114,36 mm	Minimum rib diameter outer ring
d ₁	94,35 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ2215-E	L-washer
----------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia