



FAG

NJ2309-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	100 mm	Outside diameter
B	36 mm	Width
C _r	163.000 N	Basic dynamic load rating, radial
C _{0r}	154.000 N	Basic static load rating, radial
C _{ur}	28.500 N	Fatigue load limit, radial
n _G	12.800 1/min	Limiting speed
n _{gr}	5.200 1/min	Reference speed
≈m	1,43 kg	Masa



Mounting dimensions

d _a min	54 mm	Minimum diameter shaft shoulder
d _a max	57 mm	Maximum diameter of shaft shoulder
D _a max	91 mm	Maximum diameter of housing shoulder
d _c min	66 mm	Minimum shaft shoulder

r_a max 1,5 mm Maximum recess radius

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
r _{1 min}	1,5 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
E	88,5 mm	Raceway diameter outer ring
F	58,5 mm	Raceway diameter inner ring
D _{1 min}	84,12 mm	Minimum rib diameter outer ring
d ₁	64,4 mm	Maximum rib diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

HJ2309-E L-washer

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia