



FAG

NJ2315-E-XL-M1A-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1A, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	160 mm	Outside diameter
B	55 mm	Width
C _r	390.000 N	Basic dynamic load rating, radial
C _{0r}	395.000 N	Basic static load rating, radial
C _{ur}	73.000 N	Fatigue load limit, radial
n _G	7.600 1/min	Limiting speed
n _{gr}	3.550 1/min	Reference speed
≈m	5,6 kg	Masa



Mounting dimensions

d a min	87 mm	Minimum diameter shaft shoulder
d a max	93 mm	Maximum diameter of shaft shoulder
D a max	148 mm	Maximum diameter of housing shoulder
d c min	106 mm	Minimum shaft shoulder
r a max	2 mm	Maximum recess radius

Dimensions

r min	2,1 mm	Minimum chamfer dimension
r 1 min	2,1 mm	Minimum chamfer dimension
s	4,2 mm	Axial displacement
E	143 mm	Raceway diameter outer ring
F	95 mm	Raceway diameter inner ring
D 1 min	136,24 mm	Minimum rib diameter outer ring
d 1	104,1 mm	Maximum rib diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Additional information

HJ2315-E	L-washer
----------	----------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia