



FAG

NJ2348-EX-TB-MPAX-ILR-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ...E...MPAX-ILR, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	MPAX	One Piece Brass Cage Lip Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	500 mm	Outside diameter
B	155 mm	Width
C _r	3.200.000 N	Basic dynamic load rating, radial
C _{0r}	3.750.000 N	Basic static load rating, radial
C _{ur}	380.000 N	Fatigue load limit, radial
n _G	1.940 1/min	Limiting speed
n _{gr}	750 1/min	Reference speed
≈m	152 kg	Masa

Mounting dimensions

d _{a max}	301 mm	Maximum diameter of shaft shoulder
D _{a max}	480 mm	Maximum diameter of housing shoulder



Dimensions

r min	5 mm	Minimum chamfer dimension
r 1 min	5 mm	Minimum chamfer dimension
s	13,3 mm	Axial displacement
E	447 mm	Raceway diameter outer ring
F	303 mm	Raceway diameter inner ring
D 1 min	418,2 mm	Minimum rib diameter outer ring
d 1	331,8 mm	Maximum rib diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia
- 

Łożysko gabarytowe