



FAG

NJ236-E-XL-M1-C4

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne




Twoja aktualna wersja produktu

|                           |              |                                    |
|---------------------------|--------------|------------------------------------|
| Design                    | E            | Increased Capacity Design          |
| Cage                      | M1           | Two Piece Brass Cage Roller Guided |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3  |
| Tolerance class           | PN           | Normal (ISO 492:2023)              |
| Number of rows            | 1            | Single-row design                  |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 180 mm      | Bore diameter                     |
| D               | 320 mm      | Outside diameter                  |
| B               | 52 mm       | Width                             |
| C <sub>r</sub>  | 730.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 830.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 124.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 3.750 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.850 1/min | Reference speed                   |
| ≈m              | 18,64 kg    | Masa                              |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 197 mm | Minimum diameter shaft shoulder      |
| $d_{a \max}$ | 214 mm | Maximum diameter of shaft shoulder   |
| $D_{a \max}$ | 303 mm | Maximum diameter of housing shoulder |
| $d_{c \min}$ | 233 mm | Minimum shaft shoulder               |
| $r_{a \max}$ | 3 mm   | Maximum recess radius                |

### Dimensions

|              |          |                                 |
|--------------|----------|---------------------------------|
| $r_{\min}$   | 4 mm     | Minimum chamfer dimension       |
| $r_{1 \min}$ | 4 mm     | Minimum chamfer dimension       |
| s            | 4,7 mm   | Axial displacement              |
| E            | 289 mm   | Raceway diameter outer ring     |
| F            | 217 mm   | Raceway diameter inner ring     |
| $D_{1 \min}$ | 278,6 mm | Minimum rib diameter outer ring |
| $d_1$        | 230,2 mm | Maximum rib diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

### Additional information

HJ236-E

L-washer



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe