



FAG

NJ306-E-XL-TVP2-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ...E-XL-TVP2, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	19 mm	Width
C _r	61.000 N	Basic dynamic load rating, radial
C _{0r}	48.000 N	Basic static load rating, radial
C _{ur}	7.800 N	Fatigue load limit, radial
n _G	14.200 1/min	Limiting speed
n _{gr}	8.900 1/min	Reference speed
m	0,384 kg	Masa



Mounting dimensions

$d_{a \min}$	37 mm	Minimum diameter shaft shoulder
$d_{a \max}$	40 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	65 mm	Maximum diameter of housing shoulder
$d_{c \min}$	48 mm	Minimum shaft shoulder
$r_{a \max}$	1 mm	Maximum recess radius

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
s	1,2 mm	Axial displacement
E	62,5 mm	Raceway diameter outer ring
F	40,5 mm	Raceway diameter inner ring
$D_{1 \min}$	59,2 mm	Minimum rib diameter outer ring
d_1	45 mm	Maximum rib diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Additional information

HJ306-E

L-washer

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia