



FAG

NJ308-E-XL-M1A-C3

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-M1A, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E            | Increased Capacity Design         |
| Cage                      | M1A          | Two Piece Brass Cage Lip guided   |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class           | PN           | Normal (ISO 492:2023)             |
| Number of rows            | 1            | Single-row design                 |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 40 mm        | Bore diameter                     |
| D               | 90 mm        | Outside diameter                  |
| B               | 23 mm        | Width                             |
| C <sub>r</sub>  | 96.000 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 79.000 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 13.700 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 14.200 1/min | Limiting speed                    |
| n <sub>gr</sub> | 7.100 1/min  | Reference speed                   |
| m               | 0,764 kg     | Masa                              |



Mounting dimensions

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 49 mm  | Minimum diameter shaft shoulder      |
| d <sub>a max</sub> | 51 mm  | Maximum diameter of shaft shoulder   |
| D <sub>a max</sub> | 81 mm  | Maximum diameter of housing shoulder |
| d <sub>c min</sub> | 60 mm  | Minimum shaft shoulder               |
| r <sub>a max</sub> | 1,5 mm | Maximum recess radius                |

Dimensions

|                    |          |                                 |
|--------------------|----------|---------------------------------|
| r <sub>min</sub>   | 1,5 mm   | Minimum chamfer dimension       |
| r <sub>1 min</sub> | 1,5 mm   | Minimum chamfer dimension       |
| s                  | 1,2 mm   | Axial displacement              |
| E                  | 80 mm    | Raceway diameter outer ring     |
| F                  | 52 mm    | Raceway diameter inner ring     |
| D <sub>1 min</sub> | 75,92 mm | Minimum rib diameter outer ring |
| d <sub>1</sub>     | 57,55 mm | Maximum rib diameter inner ring |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 150 °C | Operating temperature max. |

Additional information

|         |          |
|---------|----------|
| HJ308-E | L-washer |
|---------|----------|

Właściwości

|  |                                   |
|--|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |