



NK5/10-TV-XL

Needle roller bearing

Needle roller bearings NK, light series

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without	
Cage	TV	Plastic Cage made from PA66
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

Main Dimensions & Performance Data

F_w	5 mm	Under roller diameter
D	10 mm	Outside diameter
C	10 mm	Width, outer ring
C_r	2.650 N	Basic dynamic load rating, radial
C_{0r}	1.920 N	Basic static load rating, radial
C_{ur}	300 N	Fatigue load limit, radial
n_G	39.000 1/min	Limiting speed
n_{gr}	55.000 1/min	Reference speed
$\approx m$	3,1 g	Masa

Dimensions

r_{min}	0,15 mm	Minimum chamfer dimension
-----------	---------	---------------------------



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

GR5X10X2	Sealing ring
----------	--------------

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy