




NKIA5908-XL [🔗](#)

Needle roller/angular contact ball bearing

Informacje techniczne



Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 40 mm       | Bore diameter                     |
| D               | 62 mm       | Outside diameter                  |
| B               | 30 mm       | Width                             |
| C <sub>r</sub>  | 48.500 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 67.000 N    | Basic static load rating, radial  |
| C <sub>a</sub>  | 9.200 N     | Basic dynamic load rating, axial  |
| C <sub>0a</sub> | 19.400 N    | Basic static load rating, axial   |
| C <sub>ur</sub> | 11.700 N    | Fatigue limit load, radial        |
| C <sub>ur</sub> | 11.700 N    | Fatigue load limit, radial        |
| C <sub>ua</sub> | 880 N       | Fatigue load limit, axial         |
| n <sub>G</sub>  | 9.600 1/min | Limiting speed                    |
| n <sub>gr</sub> | 7.500 1/min | Reference speed                   |
| ≈m              | 314,79 g    | Masa                              |

Dimensions

|                  |        |                             |
|------------------|--------|-----------------------------|
| F                | 48 mm  | Raceway diameter inner ring |
| r <sub>min</sub> | 0,6 mm | Minimum chamfer dimension   |



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy