


NKIB5906-XL-C2

Needle roller/angular contact ball bearing

Needle roller/angular contact ball bearings
NKIB, double direction axial component

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	47 mm	Outside diameter
B	25 mm	Width
C _r	28.500 N	Basic dynamic load rating, radial
C _{0r}	35.500 N	Basic static load rating, radial
C _a	5.900 N	Basic dynamic load rating, axial
C _{0a}	11.200 N	Basic static load rating, axial
C _{ur}	6.600 N	Fatigue load limit, radial
C _{ua}	510 N	Fatigue load limit, axial
n _G	12.700 1/min	Limiting speed
n _{gr}	10.000 1/min	Reference speed
≈m	141,25 g	Masa

Dimensions

F	35 mm	Raceway diameter inner ring
C	23 mm	Width, outer ring
r _{min}	0,3 mm	Minimum chamfer dimension



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy