



**NKIS30**

## Needle roller bearing

Needle roller bearing NKIS, single row, with inner ring, outer ring with 2 bords

## Informacje techniczne



## Twoja aktualna wersja produktu

|         |          |
|---------|----------|
| Cage    | Standard |
| Coating | Without  |

## Main Dimensions &amp; Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 30 mm        | Bore diameter                     |
| D               | 52 mm        | Outside diameter                  |
| B               | 22 mm        | Width                             |
| C <sub>r</sub>  | 36.500 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 50.000 N     | Basic static load rating, radial  |
| C <sub>ur</sub> | 7.000 N      | Fatigue load limit, radial        |
| n <sub>G</sub>  | 11.700 1/min | Limiting speed                    |
| n <sub>gr</sub> | 6.400 1/min  | Reference speed                   |
| ≈m              | 189 g        | Masa                              |

## Dimensions

|                  |        |                             |
|------------------|--------|-----------------------------|
| F                | 37 mm  | Raceway diameter inner ring |
| r <sub>min</sub> | 0,6 mm | Minimum chamfer dimension   |
| s                | 1 mm   | Axial displacement          |

## Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |



### Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mala przestrzeń zabudowy