



FAG

NU1015-XL-M1A-C3 [🔗](#)

Cylindrical roller bearing

Cylindrical roller bearing NU...-XL-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	115 mm	Outside diameter
B	20 mm	Width
C _r	78.000 N	Basic dynamic load rating, radial
C _{0r}	85.000 N	Basic static load rating, radial
C _{ur}	11.000 N	Fatigue load limit, radial
n _G	11.800 1/min	Limiting speed
n _{gr}	5.200 1/min	Reference speed
≈m	0,714 kg	Masa



Mounting dimensions

d a min	80 mm	Minimum diameter shaft shoulder
d a max	83 mm	Maximum diameter of shaft shoulder
d b min	87 mm	Minimum shaft shoulder
D a max	109 mm	Maximum diameter of housing shoulder
r a max	1,1 mm	Maximum recess radius
r a1 max	1 mm	Maximum recess radius

Dimensions

r min	1,1 mm	Minimum chamfer dimension
r 1 min	1 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
E	105 mm	Raceway diameter outer ring
F	85 mm	Raceway diameter inner ring
D 1 min	101,65 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.