



FAG

NU1022-XL-M1A-P5-C4

Cylindrical roller bearing

Cylindrical roller bearing NU...-XL-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	P5	Class 5 (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	170 mm	Outside diameter
B	28 mm	Width
C _r	167.000 N	Basic dynamic load rating, radial
C _{0r}	191.000 N	Basic static load rating, radial
C _{ur}	25.000 N	Fatigue load limit, radial
n _G	7.700 1/min	Limiting speed
n _{gr}	3.850 1/min	Reference speed
m	2,248 kg	Masa



Mounting dimensions

$d_{a \min}$	116 mm	Minimum diameter shaft shoulder
$d_{a \max}$	124 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	128 mm	Minimum shaft shoulder
$D_{a \max}$	161 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius

Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
s	3,2 mm	Axial displacement
E	155 mm	Raceway diameter outer ring
F	125 mm	Raceway diameter inner ring
$D_{1 \min}$	149,7 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.