




FAG

NU1068-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing NU..-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne



Twoja aktualna wersja produktu

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	520 mm	Outside diameter
B	82 mm	Width
C _r	1.120.000 N	Basic dynamic load rating, radial
C _{0r}	1.830.000 N	Basic static load rating, radial
C _{ur}	150.000 N	Fatigue load limit, radial
n _G	2.010 1/min	Limiting speed
n _{gr}	1.190 1/min	Reference speed
≈m	62,13 kg	Masa



Mounting dimensions

d a min	357 mm	Minimum diameter shaft shoulder
d a max	381 mm	Maximum diameter of shaft shoulder
d b min	390 mm	Minimum shaft shoulder
D a max	503 mm	Maximum diameter of housing shoulder
r a max	4 mm	Maximum recess radius
r a1 max	4 mm	Maximum recess radius

Dimensions

r min	5 mm	Minimum chamfer dimension
r 1 min	5 mm	Minimum chamfer dimension
s	12,5 mm	Axial displacement
E	475 mm	Raceway diameter outer ring
F	385 mm	Raceway diameter inner ring
D 1 min	458,2 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe