



FAG

NU1080-TB-M1

Cylindrical roller bearing

Cylindrical roller bearing NU20..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	400 mm	Bore diameter
D	600 mm	Outside diameter
B	90 mm	Width
C _r	1.380.000 N	Basic dynamic load rating, radial
C _{0r}	2.330.000 N	Basic static load rating, radial
C _{ur}	176.000 N	Fatigue load limit, radial
n _G	1.730 1/min	Limiting speed
n _{gr}	980 1/min	Reference speed
≈m	87,3 kg	Masa



Mounting dimensions

$d_{a \min}$	417 mm	Minimum diameter shaft shoulder
$d_{a \max}$	445 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	455 mm	Minimum shaft shoulder
$D_{a \max}$	583 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$r_{a1 \max}$	4 mm	Maximum recess radius

Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$r_1 \min$	5 mm	Minimum chamfer dimension
s	9,5 mm	Axial displacement
E	550 mm	Raceway diameter outer ring
F	450 mm	Raceway diameter inner ring
$D_1 \min$	530 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe