



FAG


NU211-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-TVP2, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	21 mm	Width
C _r	99.000 N	Basic dynamic load rating, radial
C _{0r}	95.000 N	Basic static load rating, radial
C _{ur}	13.000 N	Fatigue load limit, radial
n _G	10.000 1/min	Limiting speed
n _{gr}	5.800 1/min	Reference speed
m	0,644 kg	Masa



Mounting dimensions

d a min	62 mm	Minimum diameter shaft shoulder
d a max	65 mm	Maximum diameter of shaft shoulder
d b min	68 mm	Minimum shaft shoulder
D a max	91 mm	Maximum diameter of housing shoulder
r a max	1,5 mm	Maximum recess radius
r a1 max	1 mm	Maximum recess radius

Dimensions

r min	1,5 mm	Minimum chamfer dimension
r 1 min	1,1 mm	Minimum chamfer dimension
s	0,8 mm	Axial displacement
E	90 mm	Raceway diameter outer ring
F	66 mm	Raceway diameter inner ring
D 1 min	86,6 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia