



FAG

NU2216-E-XL-TVP2-C3

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-TVP2, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E            | Increased Capacity Design         |
| Cage                      | TVP2         | Solid Window Cage made from PA66  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class           | PN           | Normal (ISO 492:2023)             |
| Number of rows            | 1            | Single-row design                 |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 80 mm       | Bore diameter                     |
| D               | 140 mm      | Outside diameter                  |
| B               | 33 mm       | Width                             |
| C <sub>r</sub>  | 221.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 244.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 44.500 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 7.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.400 1/min | Reference speed                   |
| m               | 1,98 kg     | Masa                              |



### Mounting dimensions

|               |        |                                      |
|---------------|--------|--------------------------------------|
| $d_{a \min}$  | 91 mm  | Minimum diameter shaft shoulder      |
| $d_{a \max}$  | 94 mm  | Maximum diameter of shaft shoulder   |
| $d_{b \min}$  | 97 mm  | Minimum shaft shoulder               |
| $D_{a \max}$  | 129 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$  | 2 mm   | Maximum recess radius                |
| $r_{a1 \max}$ | 2 mm   | Maximum recess radius                |

### Dimensions

|            |          |                                 |
|------------|----------|---------------------------------|
| $r_{\min}$ | 2 mm     | Minimum chamfer dimension       |
| $r_1 \min$ | 2 mm     | Minimum chamfer dimension       |
| s          | 1,3 mm   | Axial displacement              |
| E          | 127,3 mm | Raceway diameter outer ring     |
| F          | 95,3 mm  | Raceway diameter inner ring     |
| $D_1 \min$ | 122,9 mm | Minimum rib diameter outer ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia