



FAG

NU2234-E-XL-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	310 mm	Outside diameter
B	86 mm	Width
C _r	1.130.000 N	Basic dynamic load rating, radial
C _{0r}	1.400.000 N	Basic static load rating, radial
C _{ur}	218.000 N	Fatigue load limit, radial
n _G	3.800 1/min	Limiting speed
n _{gr}	1.470 1/min	Reference speed

≈m 28,78 kg Masa



Mounting dimensions

$d_{a \min}$	187 mm	Minimum diameter shaft shoulder
$d_{a \max}$	204 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	211 mm	Minimum shaft shoulder
$D_{a \max}$	293 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$r_{a1 \max}$	3 mm	Maximum recess radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$r_{1 \min}$	4 mm	Minimum chamfer dimension
s	7,2 mm	Axial displacement
E	281 mm	Raceway diameter outer ring
F	205 mm	Raceway diameter inner ring
$D_{1 \min}$	269,9 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia