



FAG

NU2260-EX-M1A

Cylindrical roller bearing

Cylindrical roller bearing NU..-EX-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne

Twoja aktualna wersja produktu

Design	EX	Increased Capacity Design Design Modified
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	540 mm	Outside diameter
B	140 mm	Width
C _r	2.700.000 N	Basic dynamic load rating, radial
C _{0r}	4.100.000 N	Basic static load rating, radial
C _{ur}	415.000 N	Fatigue load limit, radial
n _G	1.780 1/min	Limiting speed
n _{gr}	650 1/min	Reference speed
≈m	142,2 kg	Masa



Mounting dimensions

d a min	320 mm	Minimum diameter shaft shoulder
d a max	352 mm	Maximum diameter of shaft shoulder
d b min	358 mm	Minimum shaft shoulder
D a max	520 mm	Maximum diameter of housing shoulder
r a max	4 mm	Maximum recess radius
r a1 max	4 mm	Maximum recess radius

Dimensions

r min	5 mm	Minimum chamfer dimension
r 1 min	5 mm	Minimum chamfer dimension
s	12 mm	Axial displacement
E	495 mm	Raceway diameter outer ring
F	355 mm	Raceway diameter inner ring
D 1 min	472,6 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.