



FAG

NU2268-E-M1A

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne

Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	620 mm	Outside diameter
B	165 mm	Width
C _r	3.500.000 N	Basic dynamic load rating, radial
C _{0r}	5.700.000 N	Basic static load rating, radial
C _{ur}	550.000 N	Fatigue load limit, radial
n _G	1.580 1/min	Limiting speed
n _{gr}	520 1/min	Reference speed
≈m	227,35 kg	Masa



Mounting dimensions

d a min	366 mm	Minimum diameter shaft shoulder
d a max	404 mm	Maximum diameter of shaft shoulder
d b min	412 mm	Minimum shaft shoulder
D a max	594 mm	Maximum diameter of housing shoulder
r a max	5 mm	Maximum recess radius
r a1 max	5 mm	Maximum recess radius

Dimensions

r min	6 mm	Minimum chamfer dimension
r 1 min	6 mm	Minimum chamfer dimension
s	13,3 mm	Axial displacement
E	558 mm	Raceway diameter outer ring
F	408 mm	Raceway diameter inner ring
D 1 min	534 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia