



FAG

NU230-E-XL-MCA-C4

Cylindrical roller bearing

Cylindrical roller bearing NU20..-E-XL-MCA, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Design	Standard	
Cage	MCA	Messing Käfig, einteilig, bordgeführt am Außenring
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	270 mm	Outside diameter
B	45 mm	Width
C _r	520.000 N	Basic dynamic load rating, radial
C _{0r}	590.000 N	Basic static load rating, radial
C _{ur}	70.000 N	Fatigue load limit, radial
n _G	4.550 1/min	Limiting speed
n _{gr}	2.350 1/min	Reference speed
m	11,48 kg	Masa



Mounting dimensions

$d_{a\ min}$	164 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	179 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	184 mm	Minimum shaft shoulder
$D_{a\ max}$	256 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,5 mm	Maximum recess radius
$r_{a1\ max}$	2,5 mm	Maximum recess radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$r_{1\ min}$	3 mm	Minimum chamfer dimension
s	4 mm	Axial displacement
E	242 mm	Raceway diameter outer ring
F	182 mm	Raceway diameter inner ring
$D_{1\ min}$	233,2 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia