



FAG

NU2314-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-TVP2, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	150 mm	Outside diameter
B	51 mm	Width
C _r	325.000 N	Basic dynamic load rating, radial
C _{0r}	325.000 N	Basic static load rating, radial
C _{ur}	61.000 N	Fatigue load limit, radial
n _G	6.300 1/min	Limiting speed
n _{gr}	3.800 1/min	Reference speed
≈m	3,96 kg	Masa



Mounting dimensions

$d_{a\ min}$	82 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	87 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	92 mm	Minimum shaft shoulder
$D_{a\ max}$	138 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum recess radius
$r_{a1\ max}$	2,1 mm	Maximum recess radius

Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
$r_{1\ min}$	2,1 mm	Minimum chamfer dimension
s	4,7 mm	Axial displacement
E	133 mm	Raceway diameter outer ring
F	89 mm	Raceway diameter inner ring
$D_{1\ min}$	126,8 mm	Minimum rib diameter outer ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia