



FAG

NU2340-EX-M1A

Cylindrical roller bearing

Cylindrical roller bearing NU..-EX-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Informacje techniczne

Twoja aktualna wersja produktu

Design	EX	Increased Capacity Design Design Modified
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	420 mm	Outside diameter
B	138 mm	Width
C _r	2.040.000 N	Basic dynamic load rating, radial
C _{0r}	2.900.000 N	Basic static load rating, radial
C _{ur}	315.000 N	Fatigue load limit, radial
n _G	2.330 1/min	Limiting speed
n _{gr}	940 1/min	Reference speed
≈m	97,5 kg	Masa



Mounting dimensions

d _{a min}	220 mm	Minimum diameter shaft shoulder
d _{a max}	250,7 mm	Maximum diameter of shaft shoulder
d _{b min}	255,3 mm	Minimum shaft shoulder
D _{a max}	400 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius
r _{a1 max}	4 mm	Maximum recess radius

Dimensions

r _{min}	5 mm	Minimum chamfer dimension
r _{1 min}	5 mm	Minimum chamfer dimension
s	11,3 mm	Axial displacement
E	377 mm	Raceway diameter outer ring
F	253 mm	Raceway diameter inner ring
D _{1 min}	356,9 mm	Minimum rib diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.